



## Compact 1U rack-console

# 17" KVM rack console

The 17" KVM Rack console includes a keyboard, TFT monitor and touchpad, occupying only one height unit (1U) in a 19" rack. It can be connected to an optional KVM switch, opening up additional units of rack space while simplifying the administration of rack-mounted servers.



- 17" TFT flat color screen monitor (1280 x 1024)
- Standard 88-button keyboard and Microsoft-compatible touchpad with double-click
- Display and keyboard protected when pushed in
- Tray locks for transport safety

### Simplified management

The Bull KVM rack console contains a 17" TFT monitor, a complete keyboard and an additional touchpad which can be connected to the various servers accommodated in one single rack through KVM switches. This helps create an ergonomically optimized workplace while ensuring simplified management and maintenance thus providing an excellent price/performance ratio.

### Space saving

The 17" KVM rack console is implemented as a slide-in tray and occupies only a single height unit (1U) in a rack. Usually a standard 17" monitor takes up 9 height units (9U) of valuable space, and the keyboard with its mouse at least an additional height unit. These units

could be put to better use to accommodate more servers or storage subsystems or a UPS. The compact dimensions of the Bull 17" KVM rack console allow it to be used where space and environmental conditions would not allow a conventional CRT monitor to be used, i.e. air-conditioned rooms or machine-oriented applications.

### Ergonomic design

The TFT monitor has an adjustable tilting angle and is mounted behind the keyboard with its integrated touchpad. When not in use, the monitor can be folded into the tray. When pulled out, the tray locks into place.

### DESIGN

Form factor	Rackmounted
Mountable in	1U

### DISPLAY

Display Type	17" LCD TFT (SXGA)
Screen diagonal	17"
Viewable diagonal	17"
Viewing Angle	130° (horizontal) / 130° (vertical)
Resolution	1280 x 1024 pixels
Response Time (ms)	12ms
Max # of colors	16.2M
Brightness (cd/m <sup>2</sup> )	260
Contrast Ratio (ms)	500:1
Input Video Signal	SUB D-15polig VGA

### KEYBOARD

Layout	International, French, German, Italian
Nb of keys	88
Mouse functions	Integrated touchpad

### POWER REQUIREMENTS

Voltage	110-240 V
Frequency	50-60 Hz
Power Type	IEC 320
Power Consumption	30 W max.

### PHYSICAL SPECIFICATION

Size (HxWxD)	44 x 485 x 395 mm
Weight	12,2 Kg

### REGULATORY & SAFETY

Regulatory compliance	CE, 89/336/EEC, EN 55022/ Class B, EN 55024, EN 61000-3-2, EN 61000-3-3 73/23/EEC, FCC class B, UL 60950
-----------------------	--

### WARRANTY

Standard warranty	3 Year on-site
-------------------	----------------

Bull SAS - Bull acknowledges the rights of proprietors of trademarks mentioned herein. Bull reserves the right to modify this document at any time without notice. Some offers or parts of offers described in this document may not be available in your country. Please consult your local Bull correspondent for information regarding the offers which may be available in your country. All trademarks and registered trademarks are the property of their respective owners.

Bull SAS - rue Jean Jaurès - 78340 Les Clayes-sous-Bois – France  
UK : Maxted Road, Hemel Hempstead, Herts HP2 7DZ  
USA : 300 Concord Road, Billerica, MA 01821